



2014 DIGITAL AND CONVENTIONAL RX FRAME PARAMETERS & MEASUREMENTS

Wiley X, Inc.
7800 Patterson Pass Rd.
Livermore, CA 94550

Phone: (888) 210-8926 Fax:
(925) 583-2970
www.wileyx.com

LEGEND

A = Dimensions Between Horizontal Tangents
B = Dimensions Between Vertical Tangents
DBL = Distance Between Lenses
TEMPLE = Length of Temples
ED = Minimum Diameter Lens That Will Fit Frame

| FRAME NAME AND SERIES | POWER RANGE (Power Range=Sph+Cyl) Cyl must be (-) Max Cyl (+) or (-) 4.00 | SINGLE VISION MINIMUM PD | BIFOCAL FT28** (ADD 1.00 TO 3.00) (Seg. Ht. 8 to 20) MINIMUM PD | PROGRESSIVE (ADD 1.00 to 3.50) (Seg. Ht. 14 to 26) MINIMUM PD | ADD POWER RANGE | | | | | |
|--------------------------------------|--|-----------------------------|--|--|-----------------|----|----|-----|--------|----|
| | | | | | | A | B | DBL | TEMPLE | ED |
| CLIMATE CONTROL SERIES | | | | | | | | | | |
| AIRRAE | | | | | | | | | | |
| Digital Surfacing | -5.00 to +4.00 | 56 | N/A | 60 | 1.00 to 3.50 | 61 | 37 | 18 | 124 | 62 |
| Conventional Surfacing | -4.00 to +3.00** | 58 | 60 | 62 | 1.00 to 3.00 | | | | | |
| BLINK | | | | | | | | | | |
| Digital Surfacing | -5.00 to +4.00 | 56 | N/A | 58 | 1.00 to 3.50 | 61 | 35 | 17 | 120 | 63 |
| Conventional Surfacing | -4.00 to +3.00** | 58 | 60 | 62 | 1.00 to 3.00 | | | | | |
| BRICK | | | | | | | | | | |
| Digital Surfacing | -4.00 to +4.00 | 56 | N/A | 58 | 1.00 to 3.50 | 63 | 39 | 18 | 120 | 65 |
| Conventional Surfacing | -4.00 to +3.00** | 58 | 64 | 64 | 1.00 to 3.00 | | | | | |
| JAKE | | | | | | | | | | |
| Digital Surfacing | -4.00 to +3.00 | 56 | N/A | 60 | 1.00 to 3.50 | 64 | 39 | 15 | 120 | 68 |
| Conventional Surfacing | -4.00 to +2.00 | 58 | 64 | 64 | 1.00 to 3.00 | | | | | |
| WX ARROW | | | | | | | | | | |
| Digital Surfacing | -5.00 to +3.00 | 58 | N/A | 58 | 1.00 to 3.50 | 62 | 37 | 16 | 118 | 65 |
| Conventional Surfacing | -4.00 to +2.00 | 60 | 62 | 64 | N/A | | | | | |
| WX ARROW RIM (DIGITAL ONLY) | | | | | | | | | | |
| Digital Surfacing | -7.00 to +5.00 | 55 | N/A | 55 | 1.00 to 3.50 | 52 | 30 | 21 | 118 | 55 |
| WX ECHO | | | | | | | | | | |
| Digital Surfacing | -4.00 to +3.00 | 56 | N/A | 62 | 1.00 to 3.50 | 68 | 38 | 18 | 115 | 69 |
| Conventional Surfacing | -4.00 to +2.00 | 58 | N/A | N/A | N/A | | | | | |
| WX ECHO RIM (DIGITAL ONLY) | | | | | | | | | | |
| Digital Surfacing | -7.00 to +5.00 | 58 | N/A | 58 | 1.00 to 3.50 | 58 | 33 | 21 | 115 | 60 |
| WX GRAVITY | | | | | | | | | | |
| Digital Surfacing | -4.00 to +3.00 | 56 | N/A | 62 | 1.00 to 3.50 | 63 | 40 | 17 | 119 | 63 |
| Conventional Surfacing | -3.00 to +2.00 | 58 | 62 | 66 | 1.00 to 3.00 | | | | | |
| WX GRAVITY RIM (DIGITAL ONLY) | | | | | | | | | | |
| Digital Surfacing | -7.00 to +5.00 | 58 | N/A | 58 | 1.00 to 3.50 | 55 | 34 | 20 | 119 | 65 |
| WX KNIFE | | | | | | | | | | |
| Digital Surfacing | -4.00 to +3.00 | 58 | N/A | 58 | 1.00 to 3.50 | 63 | 38 | 17 | 122 | 56 |
| Conventional Surfacing | -4.00 to +2.00 | 60 | N/A | 64 | N/A | | | | | |
| WX KNIFE RIM (DIGITAL ONLY) | | | | | | | | | | |
| Digital Surfacing | -7.00 to +5.00 | 55 | N/A | 56 | 1.00 to 3.50 | 52 | 31 | 22 | 122 | 65 |
| STREET SERIES | | | | | | | | | | |
| WX ABBY | | | | | | | | | | |
| Digital Surfacing | -4.00 to +3.00 | 56 | N/A | 62 | 1.00 to 3.50 | 62 | 47 | 13 | 125 | 67 |
| Conventional Surfacing | -4.00 to +3.00** | 58 | 66 | 66 | 1.00 to 3.00 | | | | | |
| WX CENSOR | | | | | | | | | | |
| Digital Surfacing | -5.00 to +3.00 | 56 | N/A | 60 | 1.00 to 3.50 | 61 | 37 | 16 | 120 | 68 |
| Conventional Surfacing | -4.00 to +3.00** | 58 | 60 | 62 | 1.00 to 3.00 | | | | | |
| WX CHELSEA | | | | | | | | | | |
| Digital Surfacing | -4.00 to +3.00 | 56 | N/A | 62 | 1.00 to 3.50 | 61 | 46 | 18 | 120 | 63 |
| Conventional Surfacing | -4.00 to +3.00** | 58 | 66 | 66 | 1.00 to 3.00 | | | | | |
| WX MOXY | | | | | | | | | | |
| Digital Surfacing | -5.00 to +3.00 | 56 | N/A | 58 | 1.00 to 3.50 | 60 | 41 | 19 | 124 | 68 |
| Conventional Surfacing | -4.00 to +2.00 | 60 | 62 | 64 | N/A | | | | | |
| WX STATIC | | | | | | | | | | |
| Digital Surfacing | -4.00 to +3.00 | 56 | N/A | 62 | 1.00 to 3.50 | 64 | 41 | 19 | 124 | 68 |
| Conventional Surfacing | -4.00 to +2.00 | 58 | 62 | 66 | 1.00 to 3.00 | | | | | |
| WX TWISTED | | | | | | | | | | |
| Digital Surfacing | -4.00 to +2.00 | 60 | N/A | 60 | 1.00 to 3.50 | 65 | 39 | 17 | 125 | 67 |
| Conventional Surfacing | -3.00 to +2.00 | 60 | 68 | 68 | 1.00 to 3.00 | | | | | |
| ACTIVE SERIES | | | | | | | | | | |
| P-17 | | | | | | | | | | |
| Digital Surfacing | -5.00 to +4.00 | 56 | N/A | 58 | 1.00 to 3.50 | 61 | 36 | 18 | 120 | 63 |
| Conventional Surfacing | -4.00 to +3.00** | 58 | 60 | 62 | 1.00 to 3.00 | | | | | |
| SLAY | | | | | | | | | | |
| Digital Surfacing | -4.00 to +3.00 | 60 | N/A | 62 | 1.00 to 3.50 | 65 | 37 | 16 | 120 | 68 |
| Conventional Surfacing | -4.00 to +2.00 | 60 | 66 | 66 | 1.00 to 3.00 | | | | | |
| WX REBEL | | | | | | | | | | |
| Digital Surfacing | -3.00 to +2.00 | 58 | N/A | 58 | 1.00 to 3.50 | 65 | 40 | 18 | 124 | 63 |
| Conventional Surfacing | <i>Not Available in Conventional</i> | | | | | | | | | |
| WX RUSH | | | | | | | | | | |
| Digital Surfacing | -5.00 to +4.00 | 56 | N/A | 58 | 1.00 to 3.50 | 62 | 37 | 15 | 125 | 61 |
| Conventional Surfacing | -4.00 to +3.00** | 58 | 60 | 60 | 1.00 to 3.00 | | | | | |


**2014 DIGITAL AND CONVENTIONAL RX FRAME
PARAMETERS & MEASUREMENTS**

 Wiley X, Inc.
7800 Patterson Pass Rd.
Livermore, CA 94550

 Phone: (888) 210-8926 Fax:
(925) 583-2970
www.wileyx.com

LEGEND

A = Dimensions Between Horizontal Tangents

B = Dimensions Between Vertical Tangents

DBL = Distance Between Lenses

TEMPLE = Length of Temples

ED = Minimum Diameter Lens That Will Fit Frame

| FRAME NAME AND SERIES | POWER RANGE (Power Range=Sph+Cyl) Cyl must be (-) Max Cyl (+) or (-) 4.00 | SINGLE VISION MINIMUM PD | BIFOCAL FT28** (ADD 1.00 TO 3.00) (Seg. Ht. 8 to 20) MINIMUM PD | PROGRESSIVE (ADD 1.00 to 3.50) (Seg. Ht. 14 to 26) MINIMUM PD | ADD POWER RANGE | | | | | |
|------------------------------------|--|-----------------------------|--|--|-----------------|----|----|-----|--------|----|
| | | | | | | A | B | DBL | TEMPLE | ED |
| ACTIVE SERIES(Con't) | | | | | | | | | | |
| ZAK | | | | | | | | | | |
| Digital Surfacing | -5.00 to +4.00 | 60 | N/A | 62 | 1.00 to 3.50 | 65 | 39 | 15 | 125 | 69 |
| Conventional Surfacing | -4.00 to +3.00** | 60 | 66 | 66 | 1.00 to 3.00 | | | | | |
| CHANGEABLE SERIES | | | | | | | | | | |
| GUARD | | | | | | | | | | |
| Digital Surfacing (SV Only) | -2.00 to +2.00 | 60 | N/A | N/A | N/A | 76 | 45 | 18 | 125 | 79 |
| Conventional Surfacing | <i>Not Available in Conventional</i> | | | | | | | | | |
| PT-1 INSERT (PTX) | | | | | | | | | | |
| Digital Surfacing | -8.00 to +6.00 | 56 | N/A | 56 | 1.00 to 3.50 | 44 | 31 | 25 | 120 | 47 |
| Conventional Surfacing | -8.00 to +5.00** | 56 | 56 | 56 | 1.00 to 3.00 | | | | | |
| PT-1 INSERT (UPLC) | | | | | | | | | | |
| Digital Surfacing | -7.00 to +5.00 | 58 | N/A | 60 | N/A | 44 | 31 | 25 | 120 | 47 |
| Conventional Surfacing | -6.00 to +4.00 | 60 | N/A | N/A | N/A | | | | | |
| ROMER 3 | | | | | | | | | | |
| Digital Surfacing | -4.00 to +3.00 | 56 | N/A | 60 | 1.00 to 3.50 | 62 | 38 | 18 | 128 | 62 |
| Conventional Surfacing | -4.00 to +3.00** | 58 | 62 | 64 | 1.00 to 3.00 | | | | | |
| SABER ADVANCED INSERT (PTX) | | | | | | | | | | |
| Digital Surfacing | -8.00 to +6.00 | 56 | N/A | 56 | 1.00 to 3.50 | 44 | 31 | 25 | 120 | 62 |
| Conventional Surfacing | -8.00 to +5.00** | 56 | 56 | 56 | 1.00 to 3.00 | | | | | |
| WX SAINT | | | | | | | | | | |
| Digital Surfacing (SV Only) | -2.00 to +2.00 | 60 | N/A | N/A | N/A | 68 | 40 | 15 | 114 | 74 |
| Conventional Surfacing | <i>Not Available in Conventional</i> | | | | | | | | | |
| WX TALON INSERT (CHX) | | | | | | | | | | |
| Digital Surfacing | -8.00 to +6.00 | 56 | N/A | 56 | 1.00 to 3.50 | 45 | 42 | 18 | 120 | 53 |
| Conventional Surfacing | -8.00 to +5.00** | 56 | 56 | 56 | 1.00 to 3.00 | | | | | |
| WX TALON INSERT (UPLC) | | | | | | | | | | |
| Digital Surfacing | -7.00 to +5.00 | 58 | N/A | 60 | N/A | 45 | 42 | 18 | 120 | 53 |
| Conventional Surfacing | -6.00 to +4.00 | 60 | N/A | N/A | N/A | | | | | |
| WX VALOR | | | | | | | | | | |
| Digital Surfacing (SV Only) | -2.00 to +2.00 | 60 | N/A | N/A | N/A | 70 | 38 | 18 | 120 | 70 |
| Conventional Surfacing | <i>Not Available in Conventional</i> | | | | | | | | | |
| WX VAPOR INSERT (UPLC) | | | | | | | | | | |
| Digital Surfacing | -7.00 to +5.00 | 58 | N/A | 60 | N/A | 41 | 31 | 24 | - | 45 |
| Conventional Surfacing | -6.00 to +4.00 | 60 | N/A | N/A | N/A | | | | | |
| XL-1 ADVANCED | | | | | | | | | | |
| Digital Surfacing | -4.00 to +3.00 | 56 | N/A | 58 | 1.00 to 3.50 | 63 | 40 | 17 | 115 | 64 |
| Conventional Surfacing | -4.00 to +3.00** | 58 | 62 | 64 | 1.00 to 3.00 | | | | | |
| GOGGLES | | | | | | | | | | |
| NERVE INSERT | | | | | | | | | | |
| Digital Surfacing | -8.00 to +6.00 | 56 | N/A | 56 | 1.00 to 3.50 | 44 | 31 | 25 | 100 | 47 |
| Conventional Surfacing | -8.00 to +5.00** | 56 | 56 | 56 | 1.00 to 3.00 | | | | | |
| SG-1 | | | | | | | | | | |
| Digital Surfacing | -5.00 to +4.00 | 56 | N/A | 62 | 1.00 to 3.50 | 60 | 36 | 24 | 130 | 62 |
| Conventional Surfacing | -4.00 to +3.00** | 58 | 62 | 64 | 1.00 to 3.00 | | | | | |
| SG-1 *** (STRAP USE) | | | | | | | | | | |
| Digital Surfacing | -6.00 to +5.00 | 58 | N/A | 60 | 1.00 to 3.50 | - | - | - | - | - |
| Conventional Surfacing (SV Only) | -5.00 to +4.00** | 60 | N/A | N/A | N/A | | | | | |
| SPEAR INSERT (CHX) | | | | | | | | | | |
| Digital Surfacing | -5.00 to +4.00 | 56 | N/A | 62 | 1.00 to 3.50 | 45 | 42 | 18 | 120 | 53 |
| Conventional Surfacing | -4.00 to +3.00** | 58 | 62 | 64 | 1.00 to 3.00 | | | | | |
| SPEAR INSERT (UPLC) | | | | | | | | | | |
| Digital Surfacing | -7.00 to +5.00 | 58 | N/A | 60 | 1.00 to 3.50 | 41 | 31 | 24 | - | 45 |
| Conventional Surfacing (SV Only) | -6.00 to +4.00 | 60 | N/A | N/A | N/A | | | | | |

** Prescription range for Conventional Transitions Lenses is -3.00 to +2.00 due to base curve availability **

***Prescriptions for the SG-1 in this range must be worn with the strap due to lens thickness.